







# TECHNICAL SPECIFICATIONS

External dimensions of mattress platform	216 cm
External dimensions of mattress platform	89 cm
Mattress platform height (no mattress)	53 86 cm
TR / ATR	+17°/-17°
Siderails length	137 cm

Siderails height above platform	40 cm
Average Stretcher Weight	167 kg
Safe Working Load	320 kg
Maximum Patient Weight	280 kg
Castor diameter	20 cm

## Customization Options

Motorization		Mattress platform		Scales*	
i-Drive Power <sup>fi</sup>	FlexiDrive <sup>fi</sup>	2-section	4-section	With scales	Without scales
Castor diameter 21 cm	Castor diameter 16 cm	Only backrest adjustment	Backrest, thighrest and calfrest adjustment Ergoframe <sup>fi</sup>	Precision 0.5 kg Multizone bed exit monitoring included	No bed exit monitoring

\* Availability may vary based on market

## REFERENCES

1. White paper: Best practice for patient transport in Sprint 200 for reducing WRMSDs. Own testing, data upon request.
2. White paper: Can plastic Sprint 200 siderails surpass steel? Own testing, data upon request.
3. White paper: Enhanced features of Sprint 200 stretcher that support the prevention of pressure injuries. Own testing, data upon request.



5SVT0EEJ80CVBSPG-\*/&50PEVD0

)HICSPPL%SWF&BT0BNBLVDLMBOE

TBMFTBDW\FIFBM\BBSFDPO[



www.linnet.com